## (19) World Intellectual Property Organization

International Burcau



## 

(43) International Publication Date 27 January 2005 (27.01.2005)

PCT

## (10) International Publication Number WO 2005/008648 A1

(51) International Patent Classification7: 11/00, 20/10, 19/00

G11B 7/125.

(21) International Application Number:

PCT/IB2004/051232

(22) International Filing Date:

15 July 2004 (15.07.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data: 03102199.1


17 July 2003 (17.07.2003)

- (71) Applicant (for all designated States except US): KONIN-KLUKE PHILIPS ELECTRONICS N.V. INL/NLI: Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SCHREURS, Gerard, E., N. [BE/BE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LANGEREIS, Gerardus, R. [NL/NL]; c/o Prof. Holstlasn 6, NL-5656 AA Eindhoven (NL).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GB, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, I.C, I.K, LR, I.S, I.T, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, 7.W.
- (84) Designated States (unless otherwise Indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE,



deviation of a starting edge of a mark and/or an ending edge of a mark with respect to a nominal, position of said edge. A calculation unit (31) selects at least one predefined run length pattern and determines a correction signal (33) based on at least one statistically calculated parameter of the signed deviation value signal for the selected run length pattern. A radiation source control unit (29) controls the power of the radiation source during said writing based on the correction signal.